



GLL 3-80 CG Professional

Green supreme visibility in 3 x 360°

- 3x360° laser lines with best visibility due to high power diodes
- High accuracy up to ± 0.2 mm/m
- Contactless controlling without touching and without losing precision
- Dual power source for highest flexibility
- Receiver mode for high working range up to 120 m (dia.), compatible to new LR 7 receiver

3x360° red laser lines
with best visibility due to high power diodes



High accuracy
 ± 0.2 mm/m



Contactless controlling
without touching and without losing precision



Dual power source
for highest flexibility

GREENLASER
Technology

Receiver mode
for high working range up to 120m (diameter).
Compatible to new LR 7 receiver

Motorised line adjustment possible
with RM 3
(fits also with non-motorised RM 2)

Intuitive keypad
for easy mode selection and receiver function activation

GLL 3-80 CG PROFESSIONAL

Part number	0601063U80
Accuracy	± 0.2 mm/m
Laser diode	500 - 540 nm, < 10 mW
Operating temperature	-10 - 40 °C
Storage temperature	-20 - 70 °C
Laser class	2
Working range with receiver	120 m (diameter)
Working range without receiver	30 m (diameter)
Levelling type	Self-levelling, up to 4°
Levelling time	4 s
Dust and splash protection	IP 54
Operating time (max.)	6 h (Li-ion) and 4 h (4xAA) in 3-line mode
Tripod thread	1/4 inch, 5/8 inch
Colour of laser line	Green
Projection	3 x 360° line
Scope of supply	4 x 1.5 V LR6 (AA) batteries, AA1 alkaline battery adapter, pouch, laser target plate, carrying case, universal holder BM 1, clamp